


- ▶ Diversified barrier bars with different length available, up to 4.5 meters maximum, which offers wide scope of application.
- Driven by DC brushless motor, equipped with movable connecting rod transmission mechanism and balance spring, stable and reliable operation.
- ▶ Built-in delay auto-closing and reverse on obstacle in case of resistance.
- ▶ Support infrared photocell, loop detector, and external radar and built-in DC12V power output.
- ▶ Holes are available to fix the articulated or fence boom, and multiple boom types on one machine can be easily changed.
- ► Traffic Light interface (AC220V, can support lamp with 40W)

Specifications

Model	WD-06B4	WD-06B4H
Length of Barrier Bar (M)	4	4.5
Materials of Barrier Bar	Aluminum square pipe	
Lifting/ Falling Time	6 sec	
Operating Voltage	220±10% VAC 50 Hz	
Power	200w	
Mean Times to Failure	≥ 2.5 million times	
Ambient Temperature	Normal Model : -15°C to +60°C Low Temperature Model : -40°C to +60°C	
Case Dimension (mm)	335(W) x 962(H) x 285(D)	
Case Weight	40 kg	
Barrier Arm Weight	7 kg	8 kg



* All Specifications / colors are subject to change without notice. (V.00)





TEL / FAX +(852) 2560 7011 / +(852) 2535 6388 EMAIL mail@checol.com

ADDRESS G/F, 57 King Yip Street, Kwun Tong, Kowloon, HK





