



VIBRA-SENS

Shock and vibration detector



INTRODUCTION

VIBRA-SENS detector consists of two parts:

1. The sensor which is to be firmly attached to the protected surface.
2. The electronic card which can be placed in a safe location inside the site.

A two-wire cable connects the two parts. Once the sensor detects Vibration/Shock or Sawing, the Alarm Relay and the LED indicator in the electronic card will activate for 2 seconds.

SPECIFICATIONS

Model	VIBRA-SENS
Power Supply	5 to 15V DC
Current Drain	11mA @ 12V
Alarm Contacts Endurance	(N.C.) 0.1A/24V DC (Max)
Tamper Switch Contacts Endurance	(N.C.) 0.1A/24V DC (Max)
Alarm Time	2 Sec.

DESCRIPTION

- ▶ Detects Vibration, Shock and Sawing with unprecedented reliability.
- ▶ Only the detector's sensor should be mounted on the protected surface, while the electronic card can be placed in a safe location inside the site.
- ▶ Alerts in case of attempt to disconnect or short-circuit the sensor or its connecting cable.
- ▶ Latched memory.
- ▶ Suitable for installation on any grille type (curved or flat), as well as fences & nets.
- ▶ Mounting kit for curved grille included.
- ▶ Fast, easy installation.
- ▶ Suitable for outdoor and indoor installations.
- ▶ Adjustable detection sensitivity.
- ▶ Tamper switch.



Electronic card with the alarm relay

APPLICATIONS

- All Types of Walls
- Asbestos Roofs
- Fences & Mesh Netting
- Standard or Roll-down Shutters
- Air Conditioners
- Parked Motorcycle
- Grilles
- Safes
- Doors
- Windows
- Caravan



* All Specifications / colors are subject to change without notice. (V.01)