

# OUTDOOR SIREN

## BELL BOX WITH BACKUP BATTERY

# SL-300-B

With fully integrated sounder/strobe, self-activating cut-off timer, twin status indication, backup battery, UV resistant ABS housing, the new external bell box is designed to apply for all of the requirements of EN50131-1 -- Security Grade 2, Environmental Class III and BS4733. And it is can be compatible with most of the intruder control panels in the market.



## FEATURES

- ▶ Dual tamper protection from upper cover removal of the bell box.
- ▶ Equipped with internal 7.2V rechargeable battery, SAB mode is available.
- ▶ Red and green status LED indications for easy status confirmation.  
The indications are as follows:
  - Red and green LEDs flash alternately means system in standby mode.
  - Green LED off means no backup battery power supply.
  - Red LED off means no main power supply.
  - Red and green LEDs flashing twice quickly means siren trigger.
  - When main power is cut or tamper, red and green LEDs flash quickly, LED and the LEDs will work simultaneous.
- ▶ Piercing siren sound with superbright strobe light. Trigger signals for sounders and strobe are separate and both negative and positive inputs are compatible.
- ▶ 4 kinds of sounder timer selections. The default selection is 3 minutes. 1 minute, 15 minutes, and continuous sound are selectable with dip switch.
- ▶ External or Internal temper trigger is selectable.

## SPECIFICATIONS

Model	SL-300-B
Operating Voltage	13.5VDC
Current Consumption Standby	20mA at 13.5VDC
Backup Battery	7.2V 500mA rechargeable
Siren Current	220mA at 13.5VDC
Flash Current	180mA at 13.5VDC
Siren Output	110db for single sounder
Flash Rate	90 times per minute.
Timers	1 min, 3min, 15 min, continuous
Tamper Trigger	INT/EXT selectable
Operating Temperature	-25°C to +70°C
Housing	ABS with UV Resistant different housing colors
Lens	Blue, Red, Orange color are selectable
Dimension (mm)	130(W) x 210(H) x 78(D)
Weight	0.5 kg



\* All Specifications / colors are subject to change without notice. (V.01)