

16 Channels Digital Color Video Multiplexer LCC-MX1600



Features

- ▶ 16 cameras input simultaneously showing on a monitor as the PIP/1/4/9/16 resources picture
- ▶ High resolution, full screen 720 x 576 pixel, 256 gray scale
- ▶ Allow live display and playback VCR record video at the same time
- ▶ Video loss detection and advanced motion detection function
- ▶ Build-in time/date character generator
- ▶ 16 alarm input with 1 alarm output, alarm duration 3 ~ 99 sec
- ▶ RS232 or RS485 interface for remote control
- ▶ MUX recording mode selectable internal or external trigger



Specifications

| | | |
|---------------------------|----------------------------------|-----------------|
| Model | LCC-MX1600 | |
| Signal Format | PAL: 50Hz/ sec. | NTSC: 60Hz/sec. |
| Resolution | PAL: 720 x 576 | NTSC: 720x480 |
| Video Input | 16 Inputs, BNC 1.0Vp-p 75Ohm | |
| Video Loop Through Output | 16 Outputs, BNC 1.0Vp-p 75Ohm | |
| Main Monitor Output | 1 Output, BNC | |
| Call Monitor Output | 1 Output, BNC | |
| VCR Input | 1 Input, BNC 1.0Vp-p 75Ohm | |
| VCR Output | 1 Output, BNC 1.0Vp-p 75Ohm | |
| Alarm Input | 16 Inputs, TTL level | |
| Alarm Output | NO / NC (DB-25 Female Connector) | |
| Alarm Duration | 3 ~ 99 secretary | |
| Control Interface | RS232/ RS485 | |
| Power Consumption | DC 12V 2.5A | |
| Operating Temperature | -30°C ~ 60°C | |
| Dimension (mm) | 432(L) x 311(W) x 44(H) | |
| Weight | 2.8kg | |

* All Specifications / colors are subject to change without notice. (V.01)

