CHE-1648L (H.264 Real-time 960H DVR




Features


- H.264 compression
- HDMI, VGA outputs, and composite out (Live or Spot)
- Individual channel setup for recording & network stream (resolution / frame rate)
- Event text + image notification to FTP server and E-mail address
- Easy network : UPNP (Universal plug & play) support
- User control: Up to 20 users can be generated with various access authority
- Calendar / Time search & Thumbnail search & POS search
- Smart phone application (Live, PTZ, Search)
- E-SATA supported
- Mirror and auto-backup supported
- BNC progammable spot outs
- > Up to 4 internal SATA HDD
- Optical Driver supported




Dimensions



Rear Design



System Configuration



CHE-1648L

H.264 Real-time 960H DVR



Specifications			H.264 HDMI/VGA 1080p REAL REMOTE RECORDING RECORDING REAL REMOTE RECORDING RECORDING RECORDING REAL REMOTE RECORDING REAL REMOTE REMOTE REAL REMOTE REAL REMOTE REAL REMOTE REMO
Model			CHE-1648L
Compression Algorithm			Video : H.264, Audio : G.726
Operating System			Embedded Linux
Multi-Operation			Pentaplex (Live, Recording, Playback, Backup, Network)
Video	Input	BNC	16 CH
	Output	HDMI	1
		VGA	1
		Composite	1 (Spot or Live)
Audio	Input	RCA	16
	Output	RCA	1 (HDMI, RCA)
Interface	USB 2.0		2
	RS-485		1
	E-SATA		1
	Ethernet		1
	Sensor Input		4
	Alarm Output		1 Relay
	SATA		Max. 4 x SATA HDD or Max. 2 x SATA HDD + ODD
Live	Resolution		1920 x 1080 or 1024 x 768 (by rear DIP switch)
	Display Mode		1, 4, 9, 16
	Digital Zoom		Up to x 10
Recording	960 x 480 (960 x 576)		Up to 480(400)fps
	704 x 480 (704 x 576)		Up to 480(400)fps
	352 x 240 (352 x 288)		Up to 480(400)fps
	Max.fps/ch		30(25)fps/CH
	Mode		Manual / Continuous / Schedule / Motion / Sensor & Pre/Post, Panic
	Pre-alarm		0 ~ 30 seconds
	Post-alarm		0 ~ 120 seconds
Playback	Search		Search by Time, Calendar, Events, Thumbnail and First/Last Search
	Speed		1x, 2x, 4x, 8x, 32x, 128x
Backup	Backup Device		USB Memory Stick/HDD, DVD-RW & Backup by Network
	Backup File Format		AVI (With or Without Timestamp), PS (Playback in Backup-Viewer)
Events & Alarm			Email & FTP Notification / Alarm-out / Buzzer for Events & Video Loss
			Warning Message & Buzzer for HDD Over-Temperature
Network	Transmission		Video Dual-Stream (Local recording & Network Transmission)
			Bandwidth adjustable (64/128/256/512Kbps, 1/2/4/10Mbps, Unlimited)
	Netclient / Web (I.E.)		Live, Playback, Backup, PTZ, DVR Setup
	Mobile Viewer		Supported by Android OS, iOS (iPhone)
Power			DC12V 5A
Dimension (mm)			380(W) x 67(H) x 342(D)
Weight			5.5 kg

 $^{^{\}star}$ All Specifications / colors are subject to change without notice. (V.03)





TEL / FAX +(852) 2560 7011 / +(852) 2535 6388 EMAIL mail@checol.com

ADDRESS G/F, 57 King Yip Street, Kwun Tong, Kowloon, HK





