DVR-3000 RT Mini Series




Features

- H.264 (MPEG-4 Part 10) compression with watermarking
- Real-time Display & 200fps Recording Interval
- Alarm, Pre-alarm, Watch dog, PTZ/ Dome, Motion, Video Loss Detection, E-map function etc.
- Remote Alert Function : Telephone, Paper, Email & Remote Site DVR System
- External Storage device compatible



Dimensions



MPEG-4 PIP PT 7 Water

Specifications

a peemedalens	RECORDING Tigger	BACKUP
Model	DVR-3004-mini	DVR-3008-mini
Video input (BNC)	4	8
Audio input (RCA)	4	8
Display Speed (fps)	NTSC: 120	NTSC: 240
	PAL: 100	PAL: 200
Record Speed (fps)	NTSC: 120	NTSC: 240
	PAL: 100	PAL: 200
Recording Resolution (Pixel)	640 x 480 (NTSC) / 704 x 576 (PAL)	
Compression Format	H.264 (MPEG 4 Part 10)	
Compression Rate	Dynamic compression rate = 40:1~2400:1	
	(Automatic changes depends on the image movement)	
Recording Mode	Recycle recording mode / Program recording mode (Schedule recording per each	
	camera) / Detection area alarm triggering recording and alarm mode.	
Watch dog	Automatically restarts the computer and run checol program at the set time when the	
	system crushed.	
Alarm Function	Motion image trigger alarm / Sensor input trigger alarm / Video loss trigger alarm	
Dec Alexan Franchism	December 1 to 1 t	

Pre-Alarm Function Record the images before motion image activate recording. Record the alarm activated time. And to playback the images by choosing the Alarm Log recoding time directly. Remote Alarm Alert Captured Alarm file can be send to the preset remote computers or emails / Phone or mobile phone sound alert, pager number alert. (Optional) I/O Functions Provide multi input sensor/output port for I/O control. (Optional) PTZ / Dome Functions RS-232 (Move up, down, left, right, zoom in/out, iris and focus, preset point setting and control, auto pan function, and the cruise function.) E-map Function Provide controllable e-map to locate the camera. **Network Function** Provide connections for different network through LAN or Internet to remote one or multi systems

Live Audio Monitoring,
two way intercommunication

Remote Live Image

Activate both cameras audio recording functions and select "Live audio" from the host setup menu to get live audio monitoring and two way intercommunication.

Remote access and record the live image from the other host system and the remote site can also record images.

Remote Search Function Search for the images information, snapshots and printing function from the far end

hard disk.

Digital Zoom Playback Function When playback the record files, zoom functions of the selected area is available.

Backup Function When playback the record files, zoom functions of the selected area is available.

Backup Function Direct backup to DVD-RW / CD-RW

Watermark Support

Dimension (mm) 435(L) x 360(W) x 140(H)

 $^{^{\}star}$ All Specifications / colors are subject to change without notice. (V.02)





TEL / FAX +(852) 2560 7011 / +(852) 2535 6388 EMAIL mail@checol.com

ADDRESS G/F, 57 King Yip Street, Kwun Tong, Kowloon, HK





