

# MU-255A



## Audio Mixer 前級混音放大器

### Features

This professional machine with graceful voice captures the original sound faithfully.

### Specifications

Model	MU-255A
Power Supply	AC 230V 50Hz or DC 24V
Input	MIC × 5 (Unbalanced), AUX × 2 (Unbalanced), LINE × 3 (Balanced)
Output	LINE OUT × 2 (600Ω / Output 1V-Vpp)
REC OUT	1KΩ 0dB
Mic Input Sensitivity	3mV (Dynamic microphone) 5mV (Condenser microphone)
Sensitivity	Input 100mV / Output 1V-Vpp
Scale to Noise Ratio	> 65dB (600Ω at 0Db Output) and above
Overtone Distortion Rate	< 0.03 % ± 5
Intermodulation Distortion Rate	< 0.035 % ± 5
Tone Control	Bass ± 10dB, Treble ± 10dB
Frequency Response	20Hz (0dB) ~ 20KHz (0dB)
Dynamic range	55dB and above
Maximum output voltage	8V
Delay time	2.5 Sec
Main Color	White
Dimension	480mm(W) × 88mm(H) × 200mm(D)
Weight	3.7 Kg

港澳總代理

### CHECOL TECHNOLOGY LIMITED

TEL / FAX + (852) 2560 7011 / + (852) 2535 6388  
EMAIL mail@chechol.com  
ADDRESS G/F, 57 King Yip Street, Kwun Tong, Kowloon, HK

