

KP-140/141 PG2 Two-way Wireless Keypad



- PowerG® two-way Frequency Hopping Spread Spectrum FHSS-TDMA technology provides robustness and reliability closer than ever to wired
- Ideal for arming, disarming, emergency signaling, home automation and remote control applications
- Typical indoor range: 50-100m
- Indicates entry and exit periods even when not touched by a user
- Audible exit warning
- Visual indications for system status, troubles and memory
- Wall-mount bracket
- Battery life 4-5 years with typical use
- Proximity reader (KP-141 only) can be used even with panels that do not have a built-in proximity reader

KP-140/141 PG2 is a portable, wireless, two-way keypad for PowerMaster® systems. It enables easy arming and disarming of the alarm system and initiation of emergency, fire and panic alarms. It also controls programmable outputs (PGM) and X-10 devices from anywhere in the home or office. Two-way communication with the control panel provides homeowners with visual indication of successful command execution and system status.

Specifications:

Battery type: 3V, CR123A Lithium Battery

Weight 107g (3.4oz)

(including battery):

Operating 0°C to 49°C (32°F to 120°F). temperature:

Indoor **Operating**

environment:

Dimensions: 127 x 70 x2 4mm

(5 x 2.75 x 1in)

Certifications:

CE FC









