



Visonic®

For a secure way of life

MC-302E PG2 PowerG® Wireless Door/Window Contact with Wired Input



- Ideal for protecting doors and windows
- User-selectable operation of auxiliary input as NC or EOL (end-of-line loop with NC or NO sensors)
- Large transmission range enabling repeater-free installations
- Battery life 8 years with typical use
- Visible link quality indication shown on the device
- PowerG two-way Frequency Hopping Spread Spectrum FHSS-TDMA technology - provides robustness and reliability closer than ever to wired
- Compatible with PowerMaster systems and PowerG receivers

MC-302E PG2 is a fully supervised two-way magnetic contact transmitter, designed primarily for protecting doors and windows. This highly reliable wireless device is compatible with PowerMaster® alarm systems and is very easy to install and operate in a wide range of residential and commercial environments.

Specifications:

Battery type:	3V, CR-123 Lithium battery
Weight (including battery):	53g (1.9oz.)
Operating temperature:	0°C to 49°C (32°F to 120°F)
Operating environment:	Indoor
Dimensions:	81 x 34 x 25mm (3.19 x 1.25 x 1in)

Certifications:

CE FC

* All Specifications / colors are subject to change without notice. (V.01)

CHECOL
www.checol.com

CHECOL TECHNOLOGY LIMITED

TEL / FAX + (852) 2560 7011 / + (852) 2535 6388
EMAIL mail@checol.com
ADDRESS G/F, 57 King Yip Street, Kwun Tong, Kowloon, HK

