



Visonic®

For a secure way of life

RP-600 PG2 PowerG® Wireless Repeater



- PowerG® two-way Frequency Hopping Spread Spectrum FHSS-TDMA technology - provides robustness and reliability closer than ever to wired
- Extends the communication range between the PowerMaster® systems and other PowerG transmitters
- Transmission range is by far greater than the industry standard
- Visible link quality indication shown on the device
- Mains powered, with rechargeable 48-hour backup battery
- Compact and easy to install
- Front and back tamper protected
- LED indications for power failure, activity and installation performance diagnostics
- Compatible with PowerMaster systems and PowerG receivers

RP-600 PG2 extends the communication range between PowerMaster alarm systems and other PowerG transmitters. It receives alarm, status and control messages from the wireless devices, and sends these messages to the control panel.

Specifications:

| | |
|-----------------------------|--|
| Power supply: | 230VAC, 50Hz/9VAC, 0.35A min 120VAC, 60Hz/9VAC, 0.35A min (USA) |
| Back-up battery type: | 4.8V, 1300mAh |
| Battery back-up: | 48 hours (rechargeable) |
| Weight (including battery): | 470g (16.5oz) |
| Operating temperature: | 0°C to 49°C (32°F to 120°F) |
| Operating environment: | Indoor |
| Dimensions: | 161 x 161 x 50mm (6.44 x 6.44 x 1.75in) |

Certifications:

CE FC

* All Specifications / colors are subject to change without notice. (V.01)

CHECOL[®]
www.checol.com

CHECOL TECHNOLOGY LIMITED

TEL / FAX + (852) 2560 7011 / + (852) 2535 6388
EMAIL mail@checol.com
ADDRESS G/F, 57 King Yip Street, Kwun Tong, Kowloon, HK

