

# EPS-3322

## Electronic Patrol System

PulseStar is designed for the harshest environments. It's ideal for security guard tours, inspections, preventive maintenance checks, or any time you need to track people, items, locations, and activities. With the compact, ergonomic design and quiet operation, PulseStar indicates a successful reading with a pulse -- perfect for use on a factory floor, or in the quiet halls of a hospital.



**EPS-3322**  
PulseStar



**EPS-DL2**  
Downloader



**EPS-B5**  
Read Button

### EPS-3322

Physical	Sealed plated aluminum case that resists scratches, drops, and water
Dimension (mm)	Ø23.8 x 130.2(H)
Weight	105 g
Memory	48K RAM
Storage Temperature	-40°C to 60°C
Operating Temperature	0°C to 50°C
Humidity	5% to 95% non-condensing
Activity Log Capacity	Up to 5400 Touch Memory button ID reads
Communications	IrDA (pulse)
Battery	3-volt lithium, 2/3 "A" size
Battery Life	Up to 1 year or up to 40,000 continuous reads at default settings

### EPS-DL2

Dimension (mm)	102(L) x 102(W) x 46(D)
Weight	8.2 ounces (232.5 g)
Number of Readers	2
Power Input	12 vDC
Indicator Lights	Power, Transmit, and Receive
Serial Communications	RS-232

### EPS-B5

Physical	Water-resistant, Stainless steel case
Dimension (mm)	Ø16.3 x 5.9(H)
Weight	3.3 g
Operating Temperature	-40°C to 85°C
Battery	None
Data Storage	Unique 48-bit serial number (read only)

A complete PulseStar system includes a PulseStar reader, download station, serial port cable, Checol communications software, and Read buttons.

\* All Specifications / colors are subject to change without notice. (V.03)